



ANTI-SLIP FLOOR PAINT (Satin only)

Storage:

Protect from frost/freezing.

Where to use:

Interior wooden floors (not Teak or other oily woods) and dry concrete floors (not subject to wetting).

Preparation:

Wooden floors - Ensure the surface is sound, dry and free of dust, wax, and grease. For best results clean with a Scotchbrite pad and detergent. This product is suitable for direct application onto bare wood. Fillers - seal with ECOS Filler Sealer. Knots - treat with two liberal coats of ECOS White Knotting.

Bare concrete floors must be dry, non-dusty and free of laitance.

Previously painted floors must be clean, dry and free of loose or flaking paint and polish or wax residues. If in doubt clean with a Scotchbrite pad and sugar soap, and rinse well.

ECOS Floor Paint will key to most finishes, but a test area is always advisable.

Remove dust with a Tak rag.

WARNING: Older buildings may contain lead-based paint, which requires professional remediation if it is disturbed. If in doubt, consult with a professional from a Lead-Safe Certified Firm.

Application:

DO NOT THIN.

Stir gently and thoroughly before use and occasionally during use.

On bare concrete, the first coat can be diluted by the addition of 10% water (stir thoroughly) to help adhesion.

Two coats normally needed.

Apply generously with a well loaded brush or a narrow (6" - 10") gloss or foam roller.

Floorboards - work along the length of the boards, not across.

Use only best quality soft paint brushes/rollers.

Work progressively along, do not over-brush, do not lay off, do not go back over wet or drying painted areas.

Allow to dry at least over night (and preferably 24 hours) between coats.

Avoid applying below 41°F (5°C), above 77°F (25°C), or in direct sunlight.

Clean equipment and brushes with water.

Normally touch dry in 1-2 hours. When touch-dry the floor can be walked on (with care), but avoid scraping, scuffing or wetting for 10 days when ultimate hardness is achieved.



ANTI-SLIP FLOOR PAINT (Satin only)

Coverage:

Coverage varies with porosity but, on smooth non-porous surfaces:

110 Sq Ft per Quart (single coat)

430 Sq Ft per Gallon (single coat)

Maintenance:

Clean with a damp cloth using dilute mild detergent. Do not use harsh, abrasive or alkaline cleaners.

Do not allow pooling of water/cleaner.

Do not use floor waxes or other treatments.

Health & Safety:

Avoid contact with skin and eyes. Wash off splashes with water. Keep out of reach of children.