



## STAIN BLOCKING PRIMER

---

### Storage:

Protect from frost/freezing.

### Where to use:

This water based, solvent-free stain-block primer is highly effective and has a number of uses for concealing and blocking out difficult stains such as rusted metal, rust staining, tannin staining from hardwoods such as oak and mahogany, water staining on (for example) plaster walls & ceilings, and many other "difficult to get rid of" stains. However, this product will not block oily or tarry stains, such as those from coal fires (chimney breast) or asphalt.

This is the preferred Primer for bare Iron and Steel.

NOTE: Not ideal for exterior bare cast iron - ask for advice.

### Preparation:

The substrate should be sound, dry, non-dusty, and non-oily.

Remove any loose or flaking material.

Structural issues such as efflorescence, water ingress or rising damp, etc, must be resolved beforehand and re-plastered if needs be.

Metals - rust must be removed.

WARNING: Older buildings may contain lead-based paint, which requires professional remediation if it is disturbed. If in doubt, consult with a professional from a Lead-Safe Certified Firm.

### Application:

Do not thin. Stir gently and thoroughly before use.

Apply one or two coats (depending on the severity of the problem) by brush or roller, and allow at least 6 hours between coats. Normally touch dry in 1-2 hours.

The final coat should be pure white before recoating.

Avoid applying below 41°F (5°C).

Clean equipment and brushes with water.

Finish with any of our standard wall or trim paints - if in doubt, ask for advice.

### Coverage:

Varies with porosity but typically 110-130 Sq Ft/Quart or 430-520 Sq Ft/Gallon (one coat)

### Health & Safety:

Avoid contact with the skin and eyes. Wash off splashes with water. Keep out of the reach of children.