

### **Storage:**

Protect from frost/freezing.

### **Where to use:**

Properly prepared interior wood substrates such as floors, doors, trim, paneling, cabinets, or furniture.

### **Preparation:**

Surfaces should be clean, dry, sound and free from dirt, dust, and surface contaminants. Sand substrates first, using either fine sand paper, or a fine sanding pad. DO NOT use steel wool. Always sand in the direction of the natural grain. For staining hardwood floors, we recommend a lamb's wool applicator. Remove sanding dust with a lightly water-dampened cloth, or tack rag. Always prepare a test sample first on a scrap piece of wood before you begin to ensure a sound technique and to achieve a greater understanding of product performance. Although most stains share some similarities and characteristics, all vary slightly from one to another.

### **Application:**

Do not thin. Stir gently before use and continue stirring during application. Intermix if using multiple containers to ensure color uniformity. May be applied using a clean cotton rag, or cloth. If using a brush, maintain a wet edge and do not allow the product to puddle. Remove excess stain with a cotton cloth. Use a lamb's wool applicator for floors. Darker tones can be achieved by allowing the product to sit before wiping. A second coat may be applied after 20-30 minutes to achieve a deeper, richer look. Allow 2-4 hours before applying a clear coat. Finish with a minimum of two coats of WoodShield varnish. Avoid applying at temperatures below 41°F (5°C).

### **Clean up:**

Use warm soapy water.

### **Coverage:**

Maximum spread rate is 100-125 sq. ft. per quart, or 400-500 sq. ft. per gallon depending on substrate porosity.

### **Health & Safety:**

Avoid overexposure to skin and contact with eyes. Rinse off with water. Keep out of reach of children.