



# Application Instructions

## ECOS Exterior Satin Wall Paint

### Where to use

Exterior walls, doors, trim, paneling, cabinets, or furniture.

### Preparation

Surfaces should be clean, dry, sound and free from grease. If in doubt clean with mild detergent, rinse and dry well.

Remove all soft, dusty and loose material and abrade lightly to a feathered edge and to provide a key.

Prime with ECOS Universal Primer.

**WARNING:** Older buildings may contain lead-based paint, which requires professional remediation if it is disturbed. If in doubt, consult with a professional from a Lead-Safe Certified Firm.

### Coverage

Maximum spread rate is 80-100 sq ft per quart or 320-390 sq. ft. per gallon depending on substrate porosity.

### Application

Do not thin. Applying two coats using a brush, or a 3/8" or 1/2" shed resistant roller cover is generally best but the product can also be applied via 1800-2500 psi airless spray.

Applying two coats using a brush, or a 3/8" or 1/2" shed resistant roller cover is generally best but the product can also be applied via 1800-2500 psi airless spray.

If using a brush, maintain a wet edge and do not allow the product to puddle. Do not over brush. Allow 6-8 hours between coats. Dries to the touch in 30 minutes. Avoid applying at temperatures below 41°F (5°C).

### Clean up

Clean hands and equipment with warm soapy water.

### Storage

Protect from freezing

### Disposal

Dispose of in accordance with local ordinance.

### Health & safety

Avoid contact with skin and eyes. Wash off splashes with water.

Keep out of reach of children. Do not ingest.